


NPN Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Surface mount package ideally Suited for Automatic Insertion
- NPN

Mechanical Data

- **Package:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K3D

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	$V_{(BR)CBO}$	V	$I_C=100\mu A, I_E=0$	30
Collector-Emitter Voltage	$V_{(BR)CEO}$	V	$I_C=100\mu A, I_B=0$	30
Emitter-Base Voltage	$V_{(BR)EBO}$	V	$I_E=100\mu A, I_C=0$	10
Collector Current -Continuous	I_C	A		0.3
Total Device Dissipation	PD	mW		300
Junction Temperature	T_j	°C		150
Storage Temperature	TSTG	°C		-55 to +150

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Type	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=100\mu A, I_E=0$	30		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=100\mu A, I_B=0$	30		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=100\mu A, I_C=0$	10		
Collector cut-off current	I_{CBO}	μA	$V_{CB}=30 V, I_E=0$			0.1
Emitter cut-off current	I_{EBO}	μA	$V_{EB}=10 V, I_C=0$			0.1
DC current gain	h_{FE1}		$V_{CE}=5V, I_C=10mA$	10000		
	h_{FE2}		$V_{CE}=5V, I_C=100mA$	20000		



MMBTA14





RoHS
COMPLIANT




Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=100mA, I_B=0.1mA$			1.5
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C=100mA, I_B=0.1mA$			2
Base-emitter voltage	V_{BE}	V	$V_{CE}=5V, I_C=100mA$			2
Transition frequency	f_t	MHz	$V_{CE}=5V, I_C=10mA, f=100MHz$	125		
Collector-Emitter Voltage	C_{ob}	pF	$V_{CB}=10V, I_E=0, f=1MHz$			12

■ Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBTA14	F2	Approximate 0.008	3000	30000	120000	7" reel

■ Characteristics(Typical)






■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
theta	0°	8°	0°	8°

■SOT-23Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.